

DW-LAS-A Series Hot Air Sterilizer

High-temperature and dry heat will cause microorganism oxidation, protein denaturation, and dielectric concentration and lead microorganism poisoning. which mainly destroys the cell protoplasts by oxidation, causing the microorganisms die and kill all microorganisms within a certain heating time.

Heatures

- Mirror stainless steel chamber, with observation window, safe and convenient.
- High accuracy: Micro-computer control, LCD display, accurate and reliable.
- ♦ High efficiency: fast heating with forced convection, save more time.
- Two sets over-temperature protection system, automatically stops when exceed the temp limit.
- ◆ Equipped with leakage protector.
- ◆ Easy operation: The fan speed and timing function can be easily set in the meter.
- Movable shelf, easy for cleaning.



Specifications

Model	DW-LAS-9023A	DW-LAS-9053A	DW-LAS-9073A	DW-LAS-9123A	DW-LAS-9203A
Volume(L)	25	54	81	138	252
Voltage	220V, 50HZ				
Temp. Range	RT+10~250°C				
Temp. Resolution	0.1°C				
Temp. Stability	±1°C				
Ambient temperature	+5~40 °C				
Power (W)	650	1000	1500	1600	2450
Chamber Size(mm)	300×300×280	420×370×350	450×400×450	500×500×550	600×600×700
Exterior Size(mm)	580×500×450	710×560×530	730×530×690	780×530×800	880×730×950
Shelf	2pcs			3pcs	
Timing Range	1~9999min				