

## Kjeldahl Distillation Unit DW-K9840

DW-K9840 Auto Distiller adopts globally accepted Kjeldahl nitrogen determination method to determine nitrogen content of sample. All intelligent software design makes the sample distillation complete within minutes. The distillation and condensation automatic cleaning system makes the measurement precision further improved.

It is widely used in food processing, feed production, tobacco, livestock, soil fertility, environmental monitoring, medicine, agriculture, scientific research, teaching, quality control and other fields for the test of nitrogen or protein content, can also be used for the test of ammonium, volatile fatty acid/alkali, and so on.

### Features

1. Adding solutions automatically: automatic adding NaOH solution, acid solution, distillation water.
2. High efficiency with low cost: provide automatic function with economic solution.
3. Energy saving: low power capacity, saving cost and energy.

### Characteristics

- Display: 4.3" LCD screen
- Manual/automatic mode free changeover
- Automatic alkali liquid quantification and filling
- Automatic boric solution quantification and filling
- Automatic or manual filling mode is optional according to test need
- Distillation time can be set freely, and automatic alarming upon completion
- Automatic cleaning of control system and distiller, ensuring high measurement accuracy
- Perfect safety protection system gives distiller and tubes measurement and protection against over-temperature and over-pressure
- Intelligent design of nitrogen tube peripheral facilities include safety designs and displacement hint
- Intelligent cooling water control system achieves cooling water control and test
- Emergency stop operation is able to deal with unexpected accidents
- Automatic fault detection and intelligent audible and visual alarm system are available



### Specifications

Measuring range	0.1mg ~ 240mg N
Recovery	≥99.5%
Sample capacity	solid≤6g/sample, liquid≤16mL/sample
Distillation speed	3-6min/sample
Cooling water consumption	1.5L/min
Operating mode	Manual/automatic mode
Display modes	4.3" LCD screen
Power supply	220VAC±10%, 50Hz
Power	1.3KW
Net weight	30Kg
Dimensions	400mmx385mmx735mm

## Packing List

Sort	Name	Quantity
Main unit case	Main unit (Model DW-K9840)	1pc
Accessories	Digestion tube	10 pcs
	Power cord	1 pc
	Alkali /Water /Acid Tanks	3 pcs
	Inlet water pipe	1 pc
	Draining pipe	1 pc
	Waste receiving tank	1 pc
	Nylon cable Ties	10 pcs
	Inspection Certificate	1 pc
	User Manual	1 pc

