

I300F pH or Ion Meter

Features

- High resolution LCD display, 5.7 inches.
- Multi-reading feature allows auto-read, timed-read and continuous-read.
- Automatic/Manual temperature compensation ensures accurate results.
- Auto-hold feature senses and locks the measurement endpoint.
- Data Storage 500 sets (GLP-compliant).
- Support for USB or RS-232 communication.
- Reset feature automatically resumes all settings back to factory default options.
- IP54 waterproof.

pH

- ◆ 1-5 points calibration with Standard Recognition.
- ◆ Selectable pH buffer groups, including NIST, DIN, GB, USA.
- ◆ Automatic electrode diagnosis with pH slope and offset display.

Ion

- ◆ 1-5 points calibration.
- ◆ Selectable measurement unit, including pg/L, mg/L, g/L, mmol/L, pX, ppm, ppb, etc.
- ◆ Multi-measurement mode is supported, including Direct Reading mode.
- ◆ Over 10 methods are built-in, including F⁻, Cl⁻, Br⁻, I⁻, NO₃⁻, BF₄⁻, NH₄⁺, K⁺, Na⁺, Ca²⁺, Cu²⁺, Pb²⁺, Ag⁺ and etc., user-defined method is supported.

Includes

- ★ JB-10 stirrer
- ★ REX-5 electrode stand



Specifications

Model	I300F	
Parameters	pH/ISE/Temp.(mV/pX)	
pH	Range	-2.00 to 20.00 pH
	Resolution	0.1, 0.01 pH
	Accuracy	±0.01 pH
	Calibration Points	Up to 5
	Standard Customization	Yes
	Standard Recognition	NIST, GB, DIN, USA buffers
	Slope Limit	Yes
mV	Range	-2000.0 to 2000.0 mV
	Resolution	0.1, 0.01 mV
	Accuracy	±0.1 mV or ±0.03% of reading whichever is greater
pX	Range	-2.00 to 20.00 pX
	Resolution	0.1, 0.01 pX
	Accuracy	±0.01 pX
	Calibration Points	Up to 5

ISE	Range	1.000e-9 to 9.999e+9
	Unit	mol/L, mmol/L, g/L, mg/L, pg/F, ppm, ppb
	Resolution	Up to 4 significant digits
	Accuracy	±0.3%
	Calibration Points	Up to 5
Temperature	Range	-5.0 to 110 °C, 23.0 to 230 °F
	Unit	°C, °F
	Resolution	0.1
	Accuracy	±0.2°C
Measurement	Reading Mode	Auto Read (Fast, Medium, Slow), Timed, Continuous
	Reading Prompts	Reading, Stable, Focked
	Temp. Compensation	ATC, MTC
Data management	Data Storage	500 results each
	GUP Features	Yes
Inputs	pH Electrode	BNC(Q9)
	Temp. Probe	4-pin aviation connector
Outputs	USB	PC
	RS 232	printer
Display options	Backlight	Yes
	Auto Shutdown	1~60 min, off
	IP Rating	IP54
	Date and Time	Yes
General	Power	AC Adapter, 100-240V AC input, DC9V output
	Dimensions	242x195x68 mm
	Weight	900g (1.98 lb)
	Dimensions (Carton)	370x320x220 mm
	Weight (Gross)	3.5 kg