

MX-T6-ProE MX-T6-SE LCD Digital Tube Roller

Applications

Laboratory tube rollers provide a gentle and highly efficient rolling motions,deal for mixing blood samples, viscous substances and liquid-solid suspensions.Used in a variety of applications, such as the prevention of blood coagulation,immune precipitation, etc.

Features

1. LCD displays the speed and time
2. Rocking & rolling at variable-speed
3. Adjustable speed range from 10 to 70 rpm
4. Six roller design for gentle and efficient rolling, and easy to clean
5. DC brushless motor quiet and maintenance free
6. Cold room and incubator compatible



1. Adjustable speed range from 0 to 70 rpm
2. Six roller design for gentle and efficient rolling, and is easy to clean

Specifications

Model	MX-T6-ProE	MX-T6-SE
Amplitude	24mm	24mm
Motor type	DC motor	DC motor
Rocking motion	Rocking and rolling	Rocking and rolling
Max. load capacity	4kg	4kg
Number of rollers	6	6
Roller size[length]	280mm	280mm
Speed range	10 -70rpm	0 -70rpm
Speed display	LCD	Scale
Timer	Yes	-
Timer display	LCD	-
Time setting range	1-1199min	-
Operation mode	Continuous/timer	Continuous
Voltage,Frequency	100-240V,50/60Hz	100-240V,50/60Hz
Power	30W	25W
Dimension [DxWxH]	485x250x100mm	485x250x100mm
Weight	5.1kg	4.5kg
Permissible ambient temperature and humidity	5-40°C,80%RH	5-40°C,80%RH
Protection class	IP21	IP21