


MRF-25V368

Combined Refrigerator & Freezer



MRF-25V368 Medical Combined Refrigerator and Freezer (upper 2~8°C and lower -25°C) is widely used in hospitals blood stations and laboratories. The product has double chamber, double display, double control system, two sets of individual compressor and refrigeration system. Temperature in both chambers can be independently adjusted.

FEATURES



Multi-Scene applications

Double chamber & smaller footprint



Heated glass design

Fast defogging & no condensation



Coil evaporator

Better performance, easy maintenance



Suction circulation system

Less temp. fluctuation & better



Lockable doors

Standard locks & padlocks



Large LED displays

Easy to observe and operate, built-in USB



Precise temp. control

Temp. control accurate to 0.1°C



6 types of alarm

Audible and visual alarms





Variable space

Adjustable shelves and drawers



Eco-friendly




CFC-free refrigerant and energy-saving



STRUCTURE

Optional Accessories

Data logger
RS232 interface
RS485 interface



Refrigerator air-force circulation system keeps the chamber temperature fluctuation extremely stable at $5 \pm 3^\circ\text{C}$.

The coil evaporator evenly distributed around the cabinet. Perfect control of the temperature uniformity in the chamber

Side cross-sectional view

PARAMETER

Performance		Refrigeration System		Alarms	
Cooling method	Direct cooling	Refrigerant	R:R600 & F:R290	High/low temperature	Y
Defrost	Manual	Temp. controller	Microprocessor	Power failure	Y
Refrigerant	R600a & R290	Sensor	NTC	Sensor error	Y
Temperature range	F:-10°C ~ -25°C R:2°C ~ 8	Display	Digital display	Controller failure	Y
Ambient temperature	10~32°C	External material	SPCC sprayed steel	Door ajar	Y
Noise (db)	50	Condenser	Copper tube	Ambient temperature	Y
Electrical Data		Dimensions		Other	
Voltage frequency(V/Hz)	220V 50Hz/60Hz	Package size(W*D*H)(mm)	720*695*2015	Inside door	3 shelves & 6 drawers
Power (W)	300W	Capacity (L/cu.ft)	R:183/6.5 F:185/6.5	Remote alarm port	Optional
Current (A)	2.37 A	Exterior size(W*D*H)(mm)	720*830*1870	Access port QTY/Dia.	2/25MM
Power consumption (kWh/24h)	3.03	Interior size(W*D*H)(mm)	R:580*626*625 F:466*636*625	Internal material	SPCC sprayed steel (SUS 304 for option)