

DTY Series Multi-frequency Ultrasonic Cleaner

Product Introduction

Ultrasonic cleaning machine is to use the cavitation effect of ultrasonic waves in the cleaning liquid to accelerate the dissolution and stripping of dirt, grease and other dirt in the inner hole and blind hole of the vessel being cleaned. DRAWELL ultrasonic cleaning machine adopts imported key equipment to ensure that the instrument has the advantages of fast cleaning speed, good effect, no damage to the surface and reduced labor intensity, etc.

Features

1. Background light LCD screen
2. Microcomputer memory setting parameters
3. The ultrasonic working time set up independently
4. 0-99minutes adjustable
5. Multi-frequency conversion: 33KHz, 40KHz, 59KHz, 80KHz
6. Display working countdown time
7. Display actual temperature of the cleaning tank
8. Temperature setting range: Ambient Temperature-80°C
9. Timing range: 0-999 minutes adjustable
10. Equipped with a special stainless steel basket, reduction sound cover
11. The shell and cover are made of stainless steel
12. The equipment controlled by single-chip controller
13. With Drainage function



Parameters

Model	Inner tank (mm)L/W/H	Volume (L)	Frequency (KHz)	Ultrasonic power(W)	Heating power (W)	Rack	Drainage
DW-300DTY	300*240*150	10		300	800	√	√
DW-400DTY	300*240*200	14.4	33	400	800	√	√
DW-500DTY	500*300*150	22.5	40	500	1000	√	√
DW-600DTY	500*300*200	30	59	720	1000	√	√
DW-1000DTY	600*300*300	54	80	1000	4000	√	√
DW-1200DTY	600*400*300	72		1200	5000	√	√