

pH/Cond Pocket pH/mV/Cond/TDS/Sal/Res Tester

Bluetooth series

Features

1. The tester can measure pH, conductivity, TDS, salinity, resistivity, ORP (ORP probe optional) and temperature altogether.
2. Cloud-based data management system – allows you to record, manage and share your test data at your fingertips, never worry about data loss.
3. Comprehensive Information Display – 4 types of measurement display modes to fit in different situations.
4. The product can be used as a classic tester even without connecting to a smart phone.
5. Ability to add sample name, operator name in every data set.
6. Probe Replaceable, high cost-performance.
7. IP rating: IP67.

Probe sensor with a
pH bulb protective shield



Specifications

pH	Range	-2.00 to 16.00 pH
	Resolution	0.01 pH
	Accuracy	±0.01 pH ±1 digit
	Calibration Points	1 to 3 points
	Auto. Temperature Compensation	0 – 50 °C (32 – 122 °F)
Conductivity	Range	0 to 199.9µS/cm, 200 to 1999µS/cm, 2.0 to 20.00mS/cm
	Resolution	0.1/1µS/cm, 0.01 mS/cm
	Accuracy	±1% F.S
	Calibration Points	1 point
TDS	Range	0.1 ppm to 10.00 ppt
	TDS Factor	0.40 to 1.00
Salinity	Range	0-10ppt
Resistivity	Range	50Ω·cm to 20MΩ·cm
ORP (mV)	Range	-1000 mV to 1000 mV
	Accuracy	±0.2% F.S
Temperature	Range	0 to 50 °C (32-122 °F)
	Accuracy	±0.2 °C
Packing including		<ol style="list-style-type: none"> 1. Meter (Probe and 4×1.5V AAA alkaline batteries preinstalled) 2. 3.0 mol KCl pH/ORP soaking solution, 10mL, 1 bottle 3. Sample Vials: 30mL: 4pcs 4. Standard Cond solution 1413µS/12.88mS/cm 30mL, one for each 5. pH buffer solution: pH4.00/7.00, 30mL, one for each 6. Lanyard : 1pc 7. Hard carrying case (L/W/H: 28.0×23.0×8.2cm)