

## Pharmacy Refrigerator MPC-5V236

### Features

- Accurate temperature controller, ensure the inside temperature within 2~8°C and accuracy 0.1 °C.
- Specially designed forced-air cooling system, ensure frost-free cabinet and good temperature uniformity.
- Suggested ambient temperature 10~32°C
- Three layer toughened glass door.
- Color spray steel plate inner chamber for friendly using and easy cleaning.
- Wide available voltage range: 187V~242V

### Safety

- Safety door lock and controller setting password to prevent unauthorized access.
- Build-in back-up battery to display temperature and power alarm system for up to 8 hours without AC power.
- Auto on/off cooling fan to prevent cold air from leaking out when the door is opening.
- Visual and audible alarm system: High/low temperature, power failure, sensor error, door ajar.
- power failure protection: turn on delay of the cooling system after power failure.
- Controller error protection: the cooling system will remember the normal working cycle and keep working depending on this memory when controller or two sensor failed.

### Humanized design

- 4 casters with stopper for easy moving and fixation.
- 4 adjustable shelves for easy storing.
- Special designed service-free drainage system ensure no water in the cabinet.
- Auto on/off LED light with manual switch on control panel.



MPC-5V236

## Parameters

### Performance

Temperature Range	2~8℃
Ambient Temperature	+10~+32℃
Controller	Microprocessor
Display	Digital Display

### Refrigeration System

Compressor	1
Refrigerant	R600a
Cooling Type	Forced-air cooling
Defrost Type	Frost free

### Alarm

High/low temperature	Y
Power failure	Y
Sensor error	Y
Door ajar	Y

### Electrical Data

Power Supply(V/Hz)	220/50~60; 115/60
Rated Power(W)	254
Electrical Current(A)	1.15
Power Consumption	2.56 kwh/24h

### Dimensions

Capacity	236L
Interior Size(W*D*H)	500*420*1090mm
Exterior Size(W*D*H)	580*560*1785mm
Package Size(W*D*H)	740*690*1910mm
N.t./G.t.(approx)	75/82kg
Loading Qty(20'/40'/40'H)	24/51/51

### Accessories

Caster	4
Lamp	LED
shelf	4
Temp. Recorder Chart recorder	Optional
Test hole	Optional