

PH200EM pH Meter

Features

- High resolution LCD display screen, 6.0 inches.
- Multi-reading feature allows auto-read and continuous-read.
- Automatic/Manual temperature compensation ensures accurate results.
- Auto-hold feature senses and locks the measurement endpoint.
- Data Storage 50 sets for each parameter.
- Reset feature automatically resumes all settings back to factory default options.
- 1P54 waterproof.
- 1-3 points calibration with Standard Recognition.
- Manual temperature compensation ensures accurate results

Includes

- ★ E-201F pH composite electrode
- ★ NIST pH standard solution(4.01, 7.00, 10.01) , 50ml/vial
- ★ REX-5 electrode stand



Specifications

Model		PH200EM
Parameters		pH/mV
pH	Range	-2.00 to 18.00 pH
	Resolution	0.01pH
	Accuracy	±0.01 pH
	Calibration Points	Up to 3
	Standard Recognition	NIST buffers
mV	Range	-1999 to 1999 mV
	Resolution	1 mV
	Accuracy	±0.1%FS
Measurement	Reading Mode	Auto Read, Continuous
	Reading Prompts	Reading, Stable, Locked
	Temp. Compensation	MTC
Data management	Data Storage	50 results each
Inputs	pH Electrode	BNC(Q9)
Display options	Backlight	Yes
	Auto Shutdown	300, 600, 1200, 1800, 3600 sec., off
	IP Rating	IP54
General	Power	AC Adapter, 100-240V AC input, DC9V output
	Dimensions	242×195×68 mm
	Weight	900g (1.98 lb)
	Dimensions (Carton)	350×280×220 mm
	Weight (Gross)	2 kg