

EC200E Conductivity Meter

Features

- High resolution LCD display screen, 6.0 inches.
- Multi-reading feature allows auto-read and continuous-read.
- Automatic/Manual temperature compensation ensures accurate results.
- Auto-hold feature senses and locks the measurement endpoint.
- Data Storage 50 sets for each parameter.
- Reset feature automatically resumes all settings back to factory default options.
- IP54 waterproof.
- 1 point calibration with Standard Recognition.
- Cell constant is settable

Includes

- ★ DJS-1VTC EC electrode
- ★ 1413pS/cm EC standard solution, 50ml, 1 vial
- ★ REX-5 electrode stand



Specifications

Model		EC200E
Parameters		EC/Temp.(TDS)
Conductivity	Range	0.00 μ S/cm to 200 mS/cm
	Resolution	0.01 μ S/cm minimum, various with range selection
	Accuracy	$\pm 1.0\%$ FS
	Reference Temperature	25 $^{\circ}$ C
	Calibration Points	Up to 1
	Standard Recognition	84 μ S/cm, 1413 μ S/cm, 12.88mS/cm
TDS	Range	0.00 mg/L~100g/L
	Resolution	0.01 mg/L minimum, various with range selection
	Accuracy	$\pm 1.0\%$ FS
Temperature	Range	-5.0 to 110 $^{\circ}$ C
	Unit	$^{\circ}$ C
	Resolution	0.1 $^{\circ}$ C
	Accuracy	$\pm 0.2^{\circ}$ C
Measurement	Reading Mode	Auto Read, Continuous
	Reading Prompts	Reading, Stable, Locked
	Temp. Compensation	ATC, MTC
Data management	Data Storage	50 results each
Inputs	Conductivity with Temp. Probe	5-pin aviation connector
Display options	Backlight	Yes
	Auto Shutdown	300, 600, 1200, 1800, 3600 sec., off
	IP Rating	IP54
General	Power	AC Adapter, 100-240V AC input, DC9V output
	Dimensions	242 $\times$ 195 $\times$ 68 mm
	Weight	900g (1.98 lb)
	Dimensions (Carton)	350 $\times$ 280 $\times$ 220 mm
	Weight (Gross)	2.5 kg