

EC400F Conductivity Meter

Features

- High resolution LCD display, 5.7 inches.
- Multi-reading feature allows auto-read, timed-read and continuous-read.
- Automatic/Manual temperature compensation ensures accurate results.
- Auto-hold feature senses and locks the measurement endpoint.
- Data Storage 500 sets (GLP-compliant).
- Support for USB or RS-232 communication.
- Reset feature automatically resumes all settings back to factory default options.
- IP54 waterproof.
- 1-3 points calibration with Standard Recognition.
- Settable parameters, including cell constant, temperature compensation coefficient and TDS factor.
- Temperature compensation type (none, linear, pure water).

Includes

- ◆ DJS-1 VTC EC electrode
- ◆ 1413 μ S/cm EC standard solution, 50ml, 1 vial
- ◆ REX-5 electrode stand



Specifications

Model	EC400F
Parameters	EC/Temp.(Resistivity/TDS/Sal.)
Conductivity	Range
	0.000 μS/cm to 1000 mS/cm
	Resolution
	0.001μS/cm minimum , various with range selection
	Accuracy
	$\pm 0.5\%$ FS
Resistivity	Reference Temperature
	20, 25 °C
	Calibration Points
	Up to 3
	Standard Recognition
	84μS/cm, 1413μS/cm, 12.88mS/cm
TDS	Range
	5.00 $\Omega \cdot cm$~100.0 M$\Omega \cdot cm$
	Resolution
Salinity	0.01 $\Omega \cdot cm$ minimum
	Accuracy
	$\pm 0.5\%$ FS
Range	0.00ppm~1000ppt
	Resolution
	0.01 ppm minimum, various with range selection
Accuracy	$\pm 0.5\%$ FS
	Range
	0.0 ~ 80.0 ppt
Resolution	0.1ppt
	Accuracy
± 1ppt	± 1ppt

Temperature	Range	-10 to 135°C, 14 to 275°F
	Unit	°C, °F
	Resolution	0.1
	Accuracy	±0.1°C
Measurement	Reading Mode	Auto Read (Fast, Medium, Slow), Timed, Continuous
	Reading Prompts	Reading, Stable, Locked
	Temp. Compensation	ATC, MTC
Data management	Data Storage	500 results each
	GLP Features	Yes
Inputs	Conductivity with Temp. Probe	5-pin aviation connector
Outputs	USB	PC
	RS 232	printer
Display options	Backlight	Yes
	Auto Shutdown	1~60 min, off
	IP Rating	IP54
	Date and Time	Yes
General	Power	AC Adapter, 100-240V AC input, DC9V output
	Dimensions	242x195x68 mm
	Weight	900g (1.98 lb)
	Dimensions (Carton)	370x305x330 mm
	Weight (Gross)	2.5 kg