

## I500T pH/Ion Meter

### Features

- Color High contrast LCD touchscreen, 7.0 inches.
- Intelligent operation system provides features including user management, calibration management, method management, data management and etc.
- Multi-reading feature allows auto-read, timed-read and continuous-read.
- Automatic/Manual temperature compensation ensures accurate results.
- Data Storage 1000 sets for each parameter (GLP-compliant).
- Data analysis feature helps user review, compare and recalculate results.
- Support for USB or RS-232 communication.
- Reset feature automatically resumes all settings back to factory default options.
- IP54 waterproof.

### pH

- ◆ 1-6 points calibration with Standard Recognition.
- ◆ Selectable pH buffer groups, including DIN, NIST, USA, MERK, JIS, GB.
- ◆ Support for pH standard group customization.
- ◆ Automatic electrode diagnosis with pH slope and offset display.

### Ion

- ◆ 1-6 points calibration
- ◆ Selectable measurement unit, including pg/L, mg/L, g/L, mmol/L, pX, ppm, ppb, etc.
- ◆ Multi-measurement modes are supported, including Direct Reading mode,
- ◆ Standard Addition mode, Sample Addition mode and GRAN mode.
- ◆ Over 10 methods are built-in, including  $F^-$ ,  $Cl^-$ ,  $Br^-$ ,  $I^-$ ,  $NO_3^-$ ,  $BF_4^-$ ,  $NH_4^+$ ,  $K^+$ ,  $Na^+$ ,  $Ca^{2+}$ ,  $Cu^{2+}$ ,  $Pb^{2+}$ ,  $Ag^+$  and etc., user-defined method is supported.

### Includes

- ★ JB-10 stirrer
- ★ REX-6 electrode stand



## Specifications

<b>Model</b>		<b>I500T</b>
<b>Parameters</b>		<b>pH/ISE/Temp.(mV/ORP/pX)</b>
<b>pH</b>	<b>Range</b>	<b>-2.000 to 20.000 pH</b>
	<b>Resolution</b>	<b>0.1, 0.01, 0.001pH</b>
	<b>Accuracy</b>	<b>±0.002 pH</b>
	<b>Calibration Points</b>	<b>Up to 6</b>
	<b>Standard Customization</b>	<b>Yes</b>
	<b>Calibration Reminder</b>	<b>Yes</b>
	<b>Standard Recognition</b>	<b>NIST, GB, DIN, USA, MERK, JIS buffers</b>
	<b>Slope Limit</b>	<b>Yes</b>
<b>mV/ORP</b>	<b>Range</b>	<b>-2000.00 to 2000.00 mV</b>
	<b>Resolution</b>	<b>0.1, 0.01 mV</b>
	<b>Accuracy</b>	<b>±0.1 mV or ±0.03% of reading whichever is greater</b>
	<b>EH ORP Mode</b>	<b>Yes</b>
	<b>ORP Calibration Points</b>	<b>1 custom point (relative mV)</b>
<b>pX</b>	<b>Range</b>	<b>-2.000 to 20.000 pX</b>
	<b>Resolution</b>	<b>0.1, 0.01, 0.001 pX</b>
	<b>Accuracy</b>	<b>±0.002 pX</b>
	<b>Calibration Points</b>	<b>Up to 6</b>
<b>ISE</b>	<b>Range</b>	<b>1.000e-9 to 9.999e+9</b>
	<b>Units</b>	<b>mol/L, mmol/L, g/L, mg/L, pg/L, ppm, ppb</b>
	<b>Resolution</b>	<b>Up to 4 significant digits</b>
	<b>Accuracy</b>	<b>±0.3%</b>
	<b>Calibration Points</b>	<b>Up to 6</b>
<b>Temperature</b>	<b>Range</b>	<b>-10 to 135 °C, 14 to 275 °F</b>
	<b>Unit</b>	<b>°C, °F</b>
	<b>Resolution</b>	<b>0.1</b>
	<b>Accuracy</b>	<b>±0.1°C</b>
<b>Measurement</b>	<b>Reading Mode</b>	<b>Auto Read (Fast, Medium, Slow), Timed, Continuous</b>
	<b>Reading Prompts</b>	<b>Reading, Stable, Locked</b>
	<b>Temp. Compensation</b>	<b>ATC, MTC</b>
<b>Data management</b>	<b>Data Storage</b>	<b>1000 Groups</b>
	<b>GLP Features</b>	<b>Yes</b>
	<b>Log Management</b>	<b>Yes</b>
<b>Inputs</b>	<b>pH Electrode</b>	<b>BNC(Q9)</b>
	<b>Temp. Probe</b>	<b>4-pin aviation connector</b>
<b>Outputs</b>	<b>USB</b>	<b>USB 2.0 flash memory device, PC, scanner</b>
	<b>RS 232</b>	<b>printer, auto-sampler</b>
<b>Display options</b>	<b>Backlight</b>	<b>Yes</b>
	<b>Auto Shutdown</b>	<b>1~60 min, off</b>
	<b>IP Rating</b>	<b>IP54</b>
	<b>Date and Time</b>	<b>Yes</b>
<b>General</b>	<b>Power</b>	<b>AC Adapter, 100-240V AC input, DC24V output</b>
	<b>Dimensions</b>	<b>220×195×68 mm</b>
	<b>Weight</b>	<b>950g (2.09 lb)</b>
	<b>Dimensions (Carton)</b>	<b>370×305×330 mm</b>
	<b>Weight (Gross)</b>	<b>6.5 kg</b>