

Vortex Mixer Model: MX-S / MX-F

Vortex Mixers are ideal instruments for mixing liquid components in tubes, resuspension of cells, using an eccentric mechanism. They are widely used in biological and chemical analysis applications for vigorous re-suspension of cells or chemical pellets in tubes up to 15 ml.

Features:

- ♦ MX-S with a speed range of 0-3000rpm, stepless speed regulation.
- MX-F with the fixed Speed of 3000rpm.
- MX-S used for various mixing applications with optional adapters.
- Specially designed vacuum suction feet for body stability.
- Robust aluminum-cast construction



Parameters

	MX-S(Adjustable speed)	MX-F(Fixed speed)
Voltage	110-120V/220-230V,50/60Hz	
Power	60W	60W
Mixing motion	Orbital	Orbital
Orbital diameter	4mm	4mm
Motor type	Shaded pole motor	Shaded pole motor
Motor rating input	58W	58W
Motor rating output	10W	10W
Speed range	0-3000rpm	3000rpm
Speed display	Scale	
Run type	Touch operation/Continuous	
Dimension[WxHxD]	127×130×160mm	127×130×160mm
Weight	3.5kg	3.5kg
Permissible ambient temperature	5-40°C	5-40°C
Permissible relative humidity	80%RH	80%RH
Protection class	IP21	IP21



Accessory

Cat. No.	P/N	Descriptions	Picture
18900034	VT1.1	Standard top cup, for $<\Phi30$ mm tubes and small vessels	
18900044	VT1.2	Tube holding rod, used with VTI.3.1 to VTI.3.5	
18900505	VT1.3 VT1.3.7	Universal top plate and vacuum suction foot package(include one top plate and four suction foot)	
18900020	VTI.3.1	Tube adapter, for 48 holes test tubes, Φ6mm, used with VT1.3/ VT1.2/PS1.1	
18900021	VT1.3.2	Tube adapter, for 15 holes test tubes, Φ10mm, used with VT1.3/ VT1.2/PS1.1	
18900022	VT1.3.3	Tube adapter, for 16 holes test tubes, \$\Phi\$12mm , used with VT1.3/ VT1.2/PS1.1	
18900023	VT1.3.4	Tube adapter, for 8 holes test tubes, Φ16mm, used with VT1.3/ VT1.2/PS1.1	
18900024	VTI.3.5	Tube adapter, for 8 holes test tubes, Φ20mm, used with VT1.3/ VT1.2/PS1.1	
18900043	VT1.3.6	Platform pad, for <Ф99mm tubes and small vessels	
18900158	VT1.3.7	Rubber vacuum suction foot with screw, 1pc	